# Lee County Board Of County Commissioners Agenda Item Summary Blue Sheet No. 20060313

- 1. ACTION REQUESTED/PURPOSE: Approve the award of Project # IT060315 to waive the formal quoting process and accept three (3) quotes obtained on an informal basis to allow Solid Waste to purchase two Mack tractor trucks. The trucks will be purchased from Steele Truck Center, Inc., at the competitively quoted best grand total price of \$157,081.20. A waiver has been requested due to the urgent need for these trucks in Solid Waste's day-to-day operations.
- **2.** WHAT ACTION ACCOMPLISHES: Provides Solid Waste with two additional tractor trucks for use in its ash hauling operations.
- 3. MANAGEMENT RECOMMENDATION: Approve as stated.

4. Departmental Category: §	C8	A		5. Meetir	ng Date:	13-28-2006
6. Agenda:	7. Requireme	nt/Purpos		8. Reque		
X Consent	Stat	ute		Commiss	ioner	
Administrative	Ord	inance		Departme	ent	
Appeals	X Adn	nin. Code	AC-4-1	Division		Solid Waste
Public	Othe	er		By:	Lindsey	Sampson, Director
Walk-On				.m. *	, , , ,	the same and the

9. Background: On March 6, 2006, the Division of Purchasing received a request from Solid Waste to waive the formal quoting process – and accept 3 quotes obtained on an informal basis – to purchase two new Mack tractor trucks.

Funds are available: OB5340840100.506430

Please see attachments:

- (1) Tabulation Sheet Summarizing Quotes Received
- (2) Steele Truck Center's Quote

Department Director	Purchasing or Contracts	Human Resources	Other	County Attorney	Budget Se		County Manager/P.W. Director
314106 Januar	Malio No.	A.T.		5	CX1 106 SE 100	Grants Mgr.	Munder 3.14.06
A. Com	mission Acti						7
	Approved Deferred				2	Rec. by CoAtt	
	Deletted Denied			RECEIVED COUNTY A	BY	Date Color	
	Other			3-14-0		Time:	_[
		<u> </u>		3:50		Forwarded To:	
				COUNTY A FORWARD	ED TO:	3/14 1:10 P	
				3/14/		<u> </u>	<b></b>

INFORMAL QUOTE: IT060315			LEE COUNTY, 1	LEE COUNTY, FLORIDA TABULATION SHEET	ATTON SHEET	
BUYER: BOB FRANCESCHINI			TWC	TWO (2) MACK TRUCKS	CKS	
	STEBLE		NEXTRAN		RANEYS	
VENDORS	TRUCK	/	TRUCK		TRUCK	
	CENTER		CENTER		PARTS	
GRAND TOTAL DELIVERED PRICE	/ 8		\$ 162,686.00		\$ 163,075.00	
YEAR, MAKE AND MODEL QUOTED	2006 MACK CHN613		2006 MACK CHN613		2006 MACK CHN613	
TO BE DELIVERED WITHIN  CALENDAR DAYS	FOURTEEN		FOURTEEN		TWENTY-ONE	
QUOTE SIGNED:	YES		YES		VERBAL	
MEETS SPECIFICATIONS	YES		YES		YES	·
					4	
NO BIDS						





# **CHASSIS SPECIFICATIONS SUMMARY**

March 02, 2006

2006 MACK CHN613	AGRICULTURE Freq Turns
2000 MIACA CHING 13	 TRACTOR FOR 5TH WHEEL

Engine	MACK AC-427-ASET-CEGR 427HP	Transmission Clutch	T310 EATON/FULLER "SOLO" CL(S)79828
Front Axle Suspension	12,000# FXL12 12,000#	Rear Axie Suspension	40,000# S40 Ratio 3,86 40,000# SAL38
Tites	Front 11R24.5 Rear: 11R24.5	Wheels	24.5x8,25 ALUMINUM DISC 24.5x8,25 STEEL DISC (10 HOLE)
Ratings	GVW: 52,000# GCW: 80,000#	Fuel Tanks	LH; 80gal RH: 80gal
Fifth Wheel	BRACKET HEIGHT 7.75" FONTAINE SL3ASB SERIES	Sleeper	

# **PRICING SUMMARY**

	<u>Total Price</u>
***SELLING PRICE (ExcludingTaxes/Fees/Trade)***	\$77,820.00
Material Surcharge	\$1,200.00
Net FRET or Canadian GST Taxes	\$0.00
Tire Tax Cradit (Municipal Only)	(\$293,90)
Sales/Usage Taxes	\$0,0 <b>Ò</b>
License/Title/Etc.	
Misc Fees	\$14.50
Trade	\$0.00
***ACQUISTION COST (Include Trade if applies)***	\$78,540.60
Less Down Payment	•
BALANCE DUE Per Unit	\$78,540.60
PRICE (Total Order)	\$157,051,20
BALANCE DUE (Total Order)	\$157,081.20

Above Pricing includes hydraulic PTO and pump for operation of dump and walking floor trailer, PTO will be built to Lee County Solid Waste supplied specs. Dealer prep, FL DOT Safety equipment, and switching the tires out to 11R 22.5 is also included in above pricing.

Total Quantity: 2 Estimated Total Weight: 15,665# Reference#: EBEL001706C

Customer Signature Date

Denier Signature Date

Prepared For:
Lee County 8olid Winste 10500 Buckinghem Rd. Ft. Myers, Ft. 33905 Phone: 239-338-3302 Fax: 239-461-5871

Presented By: Ken Sposeto Stoole Truck Center, Inc. 2150 Rockfill rd Ft Myens , Florida 33916 239 334-7300



Prepared For: Lee County Solid Weste 10500 Buckinghem Rd. Ft. Myers, FL 33905 (289) 338-3302 Presented By: Steele Truck Center, Inc. 2160 Rockfill rd Ft Myere , Florida 33916 239 334-7300

Mar 1, 2008 2008 CHN813 Ref#: EBEL001708C

Page 1

#### Description

#### OREMANDELENVENICLE SEFORMATION

MITIAL REGISTRATION LOCATION, UNITED STATES, FLORIDA

TYPE OF SERVICE, MUNICIPAL

VEHICLE APPLICATION CLASS, ON-HIGHWAY CLASS "A" - Unlimited operation on concrete, asphalt, or maintained gravel/packed dirt with a maximum 3% grade; limited operation on concrete, asphalt, or maintained gravel/packed dirt with maximum 8% grade. No operation on unmaintained surfaces. (3 AXLES) 840008 MAX GVW. (4 AXLES) 800006 MAX GVW. CARRIER APPLICATION, WITH COMBINATION CRD92-63 AND 3.65 REAR AXLE RATIO, Unlimited miles on max 3% grade paved reads (max 5% miles on max 6% grade), max 5% miles on max 3% grade maintained gravel/packed dirt reads. 1050006 (47627 bg) MAX GOW. (Carrier Code USA-HS)

VEHICLE TYPE, TRACTOR FOR 5TH WHEEL

VEHICLE USE & BODY/TRAILER TYPE, AGRICULTURE.... Frog Turns

FILE STATUS, STOCK ORDER

#### BYSIFRT AXLE POSISALES PACKAGES

CHASSIS (BASE MODEL), CHINGGS 6-WHEEL TRACTOR

FRONT AXLE FORWARD POSITION

## ÉNGULETRANSINSSIÓNICLUTCH

ENGINE, MACK AC-427-ASET-CEGR 427 HP @1800 RPM 1560 LB, FT. MAX. TORQUE @ 1200 RPM

TRANSMISSION, 10 SPEED MANUAL (OVERDRIVE), MACK T310 (13,61/0.73)

CLUTCH, SELF ADJUSTING, EATON/FULLER "SOLO" CL(S)79625 15.5" TWO-PLATE WITH DAMPENED GERANIC FULL COAX S-SPRING, 4-PADDLE DRIVEN DISC AND 2.0" DIAMETER SPLINE (1700 # TORQUE CAPACITY).

# ENGINE ÉQUIPMENT

AIR COMPRESSOR, MERITÓR/WABCO 318 18.7 CFM

AIR GOVERNOR MOUNTED ON FIREWALL

ALTERNATOR, DELCO 12V 100A (228)

BATTERIES, (3) MACK 12Y M/F GROUP 31 660/1960 COA THREADED STUD TYPE W/KALAS CABLES

**BUG SCREEN, GRILLE MOUNTED** 

MACK COOLANT CONDITIONER

ENGINE BRAKE, MAOK POWERLEASH

EXHAUST, SINGLE VERTICAL EXHAUST WICURVED STACK

SINGLE, BRIGHT FINISH VERTICAL EXHAUST (INCLUDES STACK, LOWER ELBOW, AND HEAT SHIELD)

POLY-Y FAN BELT WITH AUTOMATIC TENSIONER

FLYWHEEL HOUSING, ALUMINUM

FUEL-WATER SEPARATOR, MACK WIMANUAL DRAIN VALVE (INTEGRAL WIPRIMARY FUEL FILTER)

HAND PRIMER PUMP

RADIATOR, ALUMINUM CORE

STARTER, 12 VOLT GEAR REDUCTION STARTER

# Transmission Equipment/Drivelines

INTERNAL TRANSMISSION OIL COOLER FOR MACK 1300 TRANSMISSIONS

BYNTHETIC LUBRICANT - TRANSMISSION, 75W - 90 (HENKEL BRAND)

DRIVELINE - MAIN, DANA-SPICER 1510 HD WICCOATED SPLINES

DRIVELINE - INTERAXLE, DANA-SPICER 1710 HD W/COATED OPLINES

# Lee County Solid Waste

# Refs: EBEL001706C

Page 2

#### Description

CAB (A thru G)

MACK INTEGRAL WHEATER (COMBO HEATER/AIR CONDITIONER UNIT) WIR1342 REFRIGERANT

CAB, CASS CONVENTIONAL (MELDED STEEL GALVANIZED SHELL) INCLUDES MACK RUST PREVENTATIVE

PROCEDURES

CERTIFIED WEIGHT

ENGINE SHUTOFF, KEY TYPE

FLOOR COVERING, BLACK RUBBER MATS WICLOSED CELL VINYL NITRILE FOAM BACKING

GAUGE CLUSTER, ENGINE AND TRANSMISSION OIL TEMPERATURE GAUGES

GAUGES, ENGLISH DISPLAY

GAUGE, SPEEDOMETER WITRIP ODOMETER (ELECTRONIC 1% ACCURACY)

GAUGE, ENGINE TACHOMETER (ELECTRONIC WITH HOURMETER)

GLASS - CAB WINDOW, SAFETY TINTED WINDSHIELD, SIDE AND REAR WINDOWS

#### CAB (H time 17)

HORN - AIR. (2) MACK REGTANGULAR SINGLE TRUMPET

IDENTIFICATION/CLEARANCE LIGHTS, (5) GROTE PREMIUM BRIGHT FINISH LAMPS

INTERIOR TRIM LEVEL, PREMIUM (DARK FIELDSTONE) PADDED VINYL HEADLINER WINTEGRAL HEADER CONSOLE,

PADDED VINYL DOOR PILLAR POSTS/REAR PANEL, POLY-PROPYLENE COVERED FOAM BLACK W/GRAY CARPET

INSERT DASH PANEL & KICK PANEL COVERING (FIREWALL), PNTD SILVER GRAY HEATER & FRESH AIR DUCT

COVERING, PLOW THRU HEATER DUCTS, & NON-COVERED AREAS PAINTED EXTERIOR COLOR

CHASSIS KEYED AT RANDOM - 2 KEYS

MIRRORS - CONVEX TYPE CAB DOORS, BRIGHT FINISH, LH & RH, 8" DIA. CONVEX

AM/FM STEREO CD

RADIO ANTENNA, ROOF MOUNTED

RADIO ANTENNA - CB, DUAL FIBERGLASS, MIRROR MTD

DABHBOARD MOUNTING STRAP

# CAB (S thru Z)

SEAT - DRIVER, BOSTROM TALLADEGA 015 (HI-BACK) AIR SUSPENSION

BEAT - RIDER, MACK FIXED (MID-BACK) NON-GUSPENSION

BEAT ARM RESTS, INBOARD MOUNTED ARM REST, DRIVER'S SEAT ONLY

SEAT COVERING, CLOTH WITHOUT VINYL TRIM RIDER AND DRIVER

SEAT BELTS, LAP AND BHOULDER WICAB MOUNTED SHOULDER BELT WITH FIXED D'-RING FOR DRIVER AND RIDER

STEERING COLUMN, ADJUSTABLE TILT TELESCOPE

STORAGE ACCESSORIES, PADDED VINYL WITH HEADER STORAGE SHELF WITH DOOR

MOLDED LH AND RH STORAGE POUCHES ON DRIVER & RIDER'S DOORS

**SUN VISOR, EXTERIOR, FIBERGLASS (PAINTED)** 

BUN VISOR - INTERIOR, BOTH SIDES (PADDED VINYL) WITH TICKET HOLDER

WINDSHIELD WIPERS, 2 SPEED ELECTRIC MOTOR WINTERMITTENT FEATURE

# COMMUNICATIONS SYSTEMS

W/O INFOMAX WIRELESS SRW MODULE

## FRANCE EQUIPMENT/FUEL TANKS

BUMPER - FRONT, STAINLESS STEEL CLAD ALUMINUM FLUSH MTD 112.57/2690 mm BBC (CORPORATE 0-F x 15.57) CROSSMEMBERS, STEEL Lee County Solid Waste

Ref#: EBEL001706C

...... .... ....

# Pency affion

BOXED AND TAPERED OROSSMEMBER

FIFTH WHEEL, AIR SLIDE - LH RELEASE (BOLTED TO OUTBOARD MTG ANGLES), FONTAINE SLIABS SERIES, BRACKET HEIGHT 7.75°

6TH WHEEL MOUNTING ANGLES, OUTBOARD MOUNTED ANGLES WITH MOUNTING HOLES

FLAPS - WHITEL (FRONT), BLACK POLY ARMOR

QUARTER FENDERS, STAINLESS STEEL (KONETTA) QUARTER FENDERS

TOWING DEVICE - FRONT, (2) CLEVIS

FUEL TANK - LH. 50 GALLON 22" DIAMETER UNPAINTED ALUMINUM

FUEL TANK - RH, 80 GALLON 22" DIAMETER UNPAINTED ALUMINUM

BRIGHT FINISH STAINLESS STEEL STRAPS - FUEL TANK

BRAIDED HOSE

DUAL DRAW AND RETURN FUEL SYSTEM

FRONT AXLE/EQUIPMENT/TIRES

FRONT AXLE, 12000# (5443kg) MACK FXL12

TIRES BRAND/TYPE - FRONT, GOODYEAR - TUBELESS RADIAL PLY, (2) 11R24.6 14 G G357 UNISTEEL (ALL POSITION)

WHEELS - FRONT, ALUMINUM DISC

(2) 24.543.25 ALOOA 10-HOLE HUB PILOTED

WHEELS - POLISHED (FRONT), (2) OUTSIDE SURFACE ONLY

HUSS - FRONT, FERROUS

BRAKES - FRONT, MERITOR "S" CAM TYPE 15" x 4" Q+

BRAKE DRUMS - FRONT, CAST OUTBOARD MOUNTED

DUST SHIELDS - FRONT BRAKE, OMIT

FACTORY OPTION

SHOCK ABSORBERS, FRONT

SLACK ADJUSTERS - FRONT, HALDEX - AUTOMATIC

SPRINGS - FRONT, MACK TAPERLEAF 12000F (5443kg) GROUND LOAD RATING (2 LEAF SPRING)

STEERING, TAS-65 ROSS INTEGRAL POWER

SYNTHETIC LUBRICANT - WHIL BEARINGS, FACTORY OPTION FRONT WHEEL BEARINGS LUBRICANT

REAR AXLE/EQUIPMENT/TIRES/RATIOS

REAR AXLE/SUSPENSION, 40000# (18100kg) MACK \$40, SAL38 MACK AL-401 AIR 40000# CAPACITY

TRIES BRAND/TYPE - REAR, GOODYEAR - TUBELESS RADIAL PLY, (8) 11R24.5 14 G G382 UNISTEEL (TRACTION)

CARRIEN/RATIO - REAR AXLE, MACK MALLEABLE ORDPC92/CRD83, 3.86 RATIO

WHEELB - REAR, STEEL DISC (10 HOLE)

(8) 24.5x8.25 (210 mm) ACCURIDE 10-HOLE HUB FILOTED (11 1/4" BOLT CIRCLE)(2 HAND HOLE)

HUBS-REAR, FERROUS

BRAKES - REAR, MERITOR "8" CAM 16.5"X7" C+

BRAKE DRUMS - REAR, CAST OUTBOARD MOUNTED

DUST SHIELDS - REAR BRAKE, OMIT

OIL SEALS, STEMOO (VOYAGER)

POWER DIVIDER LOCKOUT WIMMARNING LIGHT AND BUZZER (INCLUDES IN CAB MANUAL AIR VALVE)

SHOCK ABSORBERS - (4), MOUNTED ON FORWARD AND REAR AXLES EACH SIDE

SLACK ADJUSTERS - REAR, HALDEX - AUTOMATIO

SUSPENSION - AXLE SPACING, 52°

Page 3

# Reff: EBEL001706C

# Page 4

#### Description

SUSPENSION - HEIGHT CONTROL KIT, MACK

SPRING BRAKE CHAMBERS - VENDOR, MGM

**SPRING BRAKE CHAMBERS, TYPE 30/30 REAR** 

TRANSVERBE TORQUE RODS (BOTH AXLES)

## FRAME/WHEELBASE/PLATFORM

FRAME RAILS, 10.47" x 3.54" x .32" (266 x 90 x 8mm) 8TEEL Section Modulus; 15.0 cu in/RBM 1,810,000 in lbs per rail

WHEELBASE, 202" (5120 mm) WB 118" CA (2997 mm)

PLATFORM, 174" LP (mm) 56" AF (mm) USED WITH 202" WB

#### AYR/BRAKE

AIR SYSTEM VALVE VENDOR, FACTORY OPTION INCLUDES RELAY VALVE WI4 PSI CRANK PRESSURE

AIR DRYER, BENDIX "SYSTEM GUARD" AD-9 HEATED

ANTI-LOCK BRAKE BYSTEM, MERITOR/MABOO WITHOUT AUTOMATIC TRACTION CONTROL

BRAKE CONTROL VALVE SYSTEM, TWO (2) VALVE DUAL BRAKE SYSTEM - TRAILER SUPPLY AND TRACTOR-TRAILER PARK

HAND CONTROL VALVE FOR TRAILER BRAKES

WITHOUT SPRING BRAKE INVERSION VALVE

TRAILER CONNECTIONS, SEMI INCLUDES: (2) 12' AIR HOSES WIGLAD HANDS INTEGRAL GLAD HAND (BOC LHYELECTRICAL PLUG HOLDER STORAGE BRACKET, (1) 12' SEVEN WIRE CORD WISEVEN WIRE PLUG ON EACH END GROUND REACHABLE, BREAKAWAY SAFETY VALVE, AND CONSPICUITY TREATMENT TO BACK OF CAB

TRAILER AIR HOSES (12 FT DOILED TYPE)

TRAILER ELECTRICAL CORD (12 FT COILED TYPE)

TRAILER ACCESS PACKAGE WIGRAB HANDLES, ALUMINUM DECK PLATE, AND ACCESS STEP (where applicable) (Usable CA. 100\*-1117)

# EL ECTRICAL

BATTERY BOX COVERS, POLISHED ALUMINUM

BATTERY BOX - MOUNTING, STEEL BASE FORWARD OF LH FUEL TANK

DAYTIME RUNNING LIGHTS

DOUBLES TRAILER ELECTRICAL PACKAGE INCLUDES: 12 GAUGE WIRE FOR TURN SIGNALS, 12 GAUGE WIRE AND 20 AMP CIRCUIT WRELAY FOR CLEARANCE AND MARKER LAMPS, 10 GAUGE WIRE AND 20 AMP CIRCUIT WRELAY FOR STOP LAMPS, 12 GAUGE WIRE AND 20 AMP CIRCUIT WRELAY FOR TAIL LAMPS, AND 8 GAUGE WIRE FOR GROUND ELECTRIC CIRCUIT PROTECTION PACKAGE, 12 VOLT WICIRCUIT BREAKERS (HEADLAMP CIRCUIT; SAE TYPE I; ALL OTHER CIRCUITS SAE TYPE II) NEGATIVE GROUND SYSTEM

SIGNAL FLASHER TYPE, TRANSISTORIZED TURN SIGNAL, ACD TRITON

TRAILER HOOK-UP LIGHT, SINGLE (1) BACK OF CAB SEALED BEAM FLOOD LIGHT WITH IN-CAB PILOT LIGHT

# PANTAVIRYL STRIPING

PAINT/VINYL STRIPING - CAB EXTERIOR, BINGLE COLOR, MACK WHITE (HIGH GLOSS)

PAINT - CAB, URETHANE CLEAR COAT

PAINT - CAB INTERIOR, SAME COLOR AS CAB EXTERIOR COLOR

PAINT - OHASSIS RUHNING GEAR, MACK BLACK (URETHANE)

PAINT - FRONT SPOKE WHEELS, WITHOUT OPTIONAL SPOKE WHEEL PAINT

WITHOUT OPTIONAL SPOKE WHEEL PAINT

WITHOUT SPECIAL PRE-FINISHED OPTIONS

REAR WHEELS PRE-FINISHED WHITE

# Lee County Solid Weste

Ref#: EBEL001706C

Page 5

## Description

## VEHICLE ELECTRONICS

ROAD SPEED LIMIT (RSL) 74 mph

LOWER GEAR ROAD SPEED LIMIT OITH

LOWER GEAR ROAD SPEED LIMIT (LGRSL) 65 mph

92394615871

LOWER GEAR ROAD LIMIT TRANS RATIO 0.73

MAXIMUM CRUISE CONTROL SPEED 70 mph

MINIMUM CRUISE CONTROL SPEED 55 mph

ENGINE BRAKE DELAY IN CRUISE 1248

ENGINE BRAKE ENGAGEMENT DELAY IN CRUISE 2 moh

ENGINE BRAKE DIBENGAGMENT DELAY IN CRUISE

INHIBIT CRUISE CONTROL WITH PTO ON Fumbeh

CRUISE CONTROL AUTO RESUME Furnish

# **GOVERNOR SETTINGS**

**GOVERNOR TYPE Min-Max** 

HIGH IDLE (mex no load) RPM 2100 rpm

ENGINE OVERSPEED FAULT THRESHOLD 2350 rpm

LOW IDLE (min no load) RPM 650 rpm

#### TAMPER RESISTANCE

DETECT LOSS OF SIGNAL FROM MPH SENSOR Furnish

LIMIT POWER IF NO MPH SENSOR SIGNAL FURNISH

LIMIT POWER IF MPH SENSOR ELECTRICAL FAULT Omit

INCORRECT GEAR RATIO FAULT DETECTION Furnish

HOLD ELECTRICAL POWER UNTIL VEHICLE STOPS OTH

ENGINE LOAD THRESHOLD FOR NO MPH SIGNAL FAULT

FAILED MPH BENSOR ENGINE POWER LIMIT

# HAND THROTTLE CONTROL ELECTRONIC HAND THROTTLE (EHT)

EHT MAXIMUM ROAD SPEED 10 mph

EHT ENGINE SPEED LIMIT 2100 (PM)

EHT MAXIMUM SET SPEED 2100 rpm

EHT MINIMUM SET SPEED 476 rpm

EHT RAMP RATE (rpm/second)

EHT SINGLE SPEED CONTROL RPM 825 rpm

EHT BINGLE SPEED CONTROL/SSC Omit

PTO1 MAXIMUM ROAD SPEED 10 mph

PTC1 ENGINE SPEED LIMIT 2100 pm

PTO1 MAXIMUM SET SPEED 2100 rpm

PTO1 MINIMUM SET SPEED 475 rpm

PTO1 RAMP RATE

PTO1 SINGLE SPEED CONTROL RPM 1000 rpm

PTO1 ROAD SPEED LIMIT

PTO1 SINGLE SPEED CONTROL (BBC) Omit

PTO1 PARK BRAKE CHECK FOR SEC OME

PTO2 MAXIMUM ROAD SPEED 10 mph

92394615871

Les County Solid Waste

Ref#: EBEL001706C

Page 5

## Description

PTO2 ENGINE SPEED LIMIT

PTO2 MAXIMUM SET SPEED 2100 rpm

PTO2 MINIMUM SET SPEED 475 rpm

PTO2 RAMP RATE

PTO2 SINGLE SPEED CONTROL RPM 1000 rpm

PTO2 ROAD SPEED LIMIT

PTOZ SINGLE SPEED CONTROL(SSC) Omit

PTO2 PARK BRAKE CHECK FOR 88C OM

ENGINE PROTECTION BYSTEM, ENGINE SHUTDOWN AND WARNING WMANUAL OVERRIDE SWITCH

DOOLANT LEVEL SHUTDOWN OMR

COOLANT TEMPERATURE SHUTDOWN Furnish

OIL PRESSURE SHUTDOWN Furnish

TRANSMISSION TEMPERATURE SHUTDOWN OWN

AUTO TRANSMISSION TEMPERATURE SHUTDOWN OTHE

OMIT EXHAUST TEMPERATURE SHUTDOWN

VEHICLE DATA LOG - "DATAMAX", FURNISH VEHICLE DATA LOG FEATURE - "DATAMAX" BUILT-IN TRIP RECORDER (INCLLIDES COMPREHENSIVE CURRENT AND TOTAL TRIP LOG, MAINTENANCE LOG, TRIP HISTOGRAMS, DRIVER EVENT LOG, AND CUSTOMER DEFINABLE TRIP LOG. DATAMAX FEATURES ARE PROGRAMMABLE THROUGH INFOMAX PC BABED SOFTWARE WHEN AVAILABLE.)

DATA SAVE MODE WRAP

VEHICLE OVERSPEED - ALL CONDITIONS 70 mph

VEHICLE OVERSPEED - FUELED ONLY 65 mph

ENGINE OVERSPEED - BEVERE 2350 rpm .

ENGINE OVERSPEED - ALL CONDITIONS 2150 rbm

ENGINE OVERSPEED - FUELED ONLY 1850 rpm

IDLE LOGGING DELAY 2 min

# DEALER SEFORMATION

MANUALS, PEDIGREED PROTECTION PLAN TECH, SERVICE MANUAL PROVIDED

PILOT INSPECTION, WITHOUT PILOT INSPECTION

PREP FOR DELIVERY

INSTALL HYDRAULIC WET LINE KIT

STANDARD SHIPPING INSTRUCTIONS