

MIN. 4" DIA. DI

DRILL OR BURN HOLE
THROUGH PIPE

NEW YORK OF TRENCH

THOUGH PIPE

NEW YORK OF TRENCH

THOUGH PIPE

NEW YORK OF TRENCH

THOUGH PIPE

NEW YORK OF TRENCH

THE ALL-THREAD ROD SECURED


WITH GALVANIZED BOLTS AND

WASHERS, TYP.

ANCHOR PIPE

NOTES

- 1. CONNECTION TO EXITING AC WATER LINE SHALL BE ACCOMPLISHED WITH DUCTILE IRON (MJ) FITTINGS, DR-18 PVC PIPING ("SPOOL PIECE") AND TRANSITION COUPLING(S) WITH STAINLESS STEEL FASTENERS (PIPING MUST BE RESTRAINED IN ALL DIRECTIONS). ALL CUTTING OF AC PIPING SHALL BE ACCOMPLISHED WITH WET CUTTING.
- 2. FOR PRODUCTS AND MATERIALS SEE THE PROJECT SPECIFICATIONS AND QUALIFIED PRODUCTS LIST.
- 3. CONTRACTOR SHALL INSTALL A TRACING WIRE ALONG THE TRANSITION COUPLING AND VALVES.
- 4. ADD TRACER WIRE PER LCU STANDARD DETAIL G-03.
- 5. CONCRETE TO EXTEND 6" PAST ALL TEE CONNECTIONS. PLASTIC SHEETING (VISQUEEN) WRAPPED AROUND FITTING.



NOT TO SCALE